

TECHNICAL SPECIFICATIONS SHEET

TECHNICAL DETAILS	Product name	GREVY			
	Composition	33%PES,27%CV, 20%LI, 20%PC			
	Weight per Square Meter	570 g	± 5%		
	Usable Width	140 cm	± 2%		
	Roll Length	35 m			
	Thickness	2,8 mm	± 5%		
	Fabric Type	Flat weave			
	Finish				
COLOUR FASTNESS	Light	5 ISO 105-B02:2014			
	Water	4 ISO 105-E01:2013			
	Rubbing (dry/wet)	dry	4/5	wet	4 ISO 105-X12:2016
	Abrasion Resistance (Martindale)	45000 rubs ISO 12947-2:2016		grade 4 shade change after 3000 rubs	
PHYSICAL CHARACTERISTICS	Pilling Resistance	4 ISO 12945-2:2000			
	Tensile Strength	warp	1644 N	weft	953 N ISO 13934-1:2013
	Tear Strength	warp	374 N	weft	227 N ISO 13937-3:2000
	Seam Slippage	warp	4 mm	weft	5 mm ISO 13936-2:2004
	Water Repellency	ISO 23232:2009			
	Flammability	BS5852:2006			

Care Instructions



Test results were gathered from various samples and therefore represent average indicative values.