


Design: INFANTADO



**BASIC INFORMATION**

Brand	Bru	Number of colour ways	6
Tariff item number	5801370000	MID	INDEHOM16
Country of origin	India	Characteristics	Velvet
Vertical repeat cm	37.50	Vertical repeat inch	14.76
Horizontal repeat cm	36.00	Horizontal repeat inch	14.17
Face in	Yes	Full roll diameter cm	30
Full roll diameter inch	11.81	Average piece length m	35
Minimum for special colour m	1000	Delivery time weeks special lab dip	4

**CARE AND USAGE**

Care code comments Iron on reverse side

**Care codes**

Care code for washing °C Washable at 30°C extra gentle cycle Care code for bleaching Do not bleach



**Use codes**

- |               |                        |
|---------------|------------------------|
| Curtains      | Curtains and draperies |
| Upholstery ✓  | Bed covering           |
| Accessories ✓ | Maritime               |

Design: INFANTADO

FABRIC SPECIFICATIONS

Composition	64% Polyester, 36% Viscose	Average yarn number	9.62
Construction	31.88x18.90	Woven	Yes
Useable width cm	1.44	Useable width inch	56.69
Full width cm	146	Full width inch	57.48
Weight g/m <sup>2</sup>	528	Thickness mm	0.000
Colouring type	Yarn dyed	Filament or staple	100% filament
Textured or non textured	20% textured, 80% not textured		

Treatment

Bio treatment	Flame retardant
Soil and stain repellent	Brushed/emerised
Backing	Anti-bacterial/microbial
Mildew resistant	Odour resistant
Stain-free technology	PFC free
Other treatment	No treatment ✓

Type of finish

Calender	Sanforized
Thermofixed	Washed
Airo ✓	Stenter

Type of print or dye

Disperse	Reactive ✓
Vat	Pigment

Weaving type

Plain	Twill
Satin	Dobby
Jacquard ✓	Pile
Other	

Design: INFANTADO

FABRIC TYPE

There are no technical details for this section.

ENVIRONMENTAL STANDARDS



Prop 65

Yes

FR STANDARDS

BS5852 source 0  
FMVSS 302 Pass

Yes  
Yes

CAL 117 Complies  
NFPA 260

Yes  
Yes

Design: INFANTADO

**MECHANICAL PERFORMANCE**

Martindale rubs	20,000	Colour fastness to light	4
Wyzenbeek double rubs	20,000	Pilling	4
Brush pilling	4	Wyzenbeek wire screen double rubs - residential use, stopped after 15 000 double rubs	15,000
Wyzenbeek cotton duck type general upholstery	Yes	Wyzenbeek wire screen heavy duty	Yes
<b>Colour fastness to light - ISO 105-B02</b>			
Colour fastness to light	4		
<b>Colour fastness to water - ISO 105-E01</b>			
Colour fastness to water	5		
<b>Colour fastness to dry rub - ISO 105-X12</b>			
Colour fastness dry rub	4-5		
<b>Colour fastness to wet rub - ISO 105-X12</b>			
Colour fastness wet rub	4-5		
<b>Colour fastness to wear - ISO 12947-2</b>			
Colour fastness to wear	4		
<b>Tearing strength - ISO 13937-3</b>			
Tearing strength warp N	280	Tearing strength weft N	84
<b>Tensile strength - ISO 13934-1</b>			
Tensile strength warp N/5cm	800	Tensile strength weft N/5cm	2000
<b>Elongation - ISO 13934-1</b>			
Elongation warp %	35.50	Elongation weft %	12.50
<b>Seam slippage - ISO 13936-2</b>			
Seam slippage warp mm	3	Seam slippage weft mm	4
<b>Dimensional stability (indicated in %) - ISO 3759</b>			
Dimensional change warp	-0.07	Dimensional change warp after ironing with steam	0.40
Dimensional change warp after ironing without steam	0.47	Dimensional change weft	-0.15
Dimensional change weft after ironing with steam	0.07	Dimensional change weft after ironing without steam	0.13

Design: INFANTADO

**WASHABILITY**

**Resistance to domestic washing 30° C, indicated in % - ISO 6330**

---

Dimensional change warp	-1.86	Dimensional change warp after ironing	-1.86
Dimensional change weft	-0.03	Dimensional change weft after ironing	-1.59
Colour fastness ISO 105 C06	4-5		

**Resistance to domestic washing 60° C, indicated in % - ISO 6330**

---

Dimensional change warp	-3.11	Dimensional change warp after ironing	-2.68
Dimensional change weft	-0.53	Dimensional change weft after ironing	-0.40
Colour fastness ISO 105 C06	4-5		

**Resistance to dry cleaning P, indicated in % - ISO 105 D01**

---

Dimensional change warp	-1.93	Dimensional change warp after ironing	-0.33
Dimensional change weft	-0.40	Dimensional change weft after ironing	-0.33
Colour fastness ISO 105 D01	4-5		

Design: INFANTADO

CONSTRUCTION

Yarn 1

Warp Composition	100% Polyester	Warp Is Filament	Yes
Warp Is Not High Tenacity	Yes	Warp Is Textured	Yes
Warp Sizes	300/450	Warp Textured	Yes
Warp Threads per cm	31.88	Warp TPM	0

Yarn 2

Weft Composition	100% Polyester	Weft Is Filament	Yes
Weft Is Not High Tenacity	Yes	Weft Sizes	950D
Weft Threads per cm	18.9	Weft TPM	0

Yarn 3

Weft Composition	100% Viscose	Weft Is Not High Tenacity	Yes
Weft Is Staple	Yes	Weft Sizes	2/24s
Weft Threads per cm	0	Weft TPM	0

DOWNLOADS / CERTIFICATES

There are no technical details for this section.