






TECHNICAL SPECIFICATIONS SHEET

| | |
|--|---|
| SERIE / SERIES | TRAVIATA |
| ANCHO / WIDTH | 140 cm |
| PESO / WEICHT | 730 gr/m |
| COMPOSICIÓN / COMPOSITION | 100% PL |
| MARTINDALE TEST | +90.000 EN ISO 12947-2 |
| SOLIDEZ A LA LUZ / COLOR FASTNESS TO LIGHT | 4 EN ISO 105-B02 |
| RESISTENCIA AL PILLING / PILLING RESISTANCE | 4/5 EN ISO 12945-2 |
| RESISTENCIA A LA TRACCION / TENSILE STRENGTH | Undimbre (warp) 1300 / Trama (Width) 3900 N |

| | |
|---|--|
|  | La temperatura máxima de lavado es de 30º / Wash at or below 30º |
|  | No usar lejía / Do not Bleach |
|  | Planchar a temperatura media, máximo 110º / Iron at medium temperature 110º |
|  | No admite limpieza en seco. Does not admit dry cleaning |
|  | No secadora / No tumble drye No centrifugar / Do not drain in a washing machine |

HIDRORREPELENTE / WATER –REPELLENT

Importante: No utilizar oxidantes ni blanqueadores ópticos.

Important; Do not use oxidants or optical brighteners.